Display
- 19-inch 4:3 TFT LCD (1280x1024)

CPU Support
- Intel® Core™ i3, i5 & i7 processors

Chipset
- Intel® H61 Express chipset (Sandy Bridge)

Memory
- 2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB Max. Supports PC3-10600 1333MHz SO-DIMM

HDD Support
- Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports

Video & Graphics
- nVidia GPU with 1GB dedicated memory or the Intel® integrated H61 Chipset, with Intel® HD Graphics (Intel® GMA HD), includes built-in support for full 1080p HD. Maximum resolution: 2560 x 1600

Networking
- Dual Gigabit (Gbe) Fast Ethernet, Realtek RTL 8111E

Audio
- Realtek ALC892 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and jack re-tasking.

I/O Ports
- 2 X USB 3.0 ports, 4 x USB 2.0 ports
- 1 x RS232 serial port, option to expand to 3 COM ports
- DVI-I monitor out port
- HDMI Full 1080p

Power Supply
- 135 Watt Medical Grade Adapter
  100 ~ 240V AC, 50-60Hz. Supports Output range:
  DC12V/19V. 5.0A/9.5A Adapters for Energy Star 5.0/UL

Touch Screen
- 5-Wire Resistive Single Touch Technology

Wireless
- Intel Centrino 802.11 agn, 2x2, dual band delivers up to 300 Mbps speed, Bluetooth 4.0

Wall Mount
- Supports both 75mm & 100mm VESA mounting holes

Expansion Slots
- Two Mini PCI-e (1xFull-size and 1xHalf-size)

Bios
- AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection

Security Lock
- Security lock slot located on the back of the system case

Swivel base
- System Base enables left/right rotation up to 60°. Tilt from -5 to 60°

Weight	• 18.1lbs
Environment	• Ambient Temperature: 0°C ~ 50°C (operating)
Relative Humidity	• 10% ~ 90% (non-condensing)
Waterproof	• IP64 Front Bezel

O/S	• Microsoft Windows 7, Windows 8, Linux
Dimensions	• 17" Wide x 15.8" Height x 3.2 Depth
Color	• White with Antimicrobial Coating
Certifications	• EN60601-1, FCC CLASS B, CE, UL60950, ES 5.2, RoHS, WEEE

Corporate Headquarters
Cybernet Manufacturing
5 Holland
Irvine, California 92618
Phone: (888) 834-4577
Fax: (949) 600-8013
www.cybernetman.com
sales@cybernetman.com
support@cybernetman.com

Cybernet Europe
Network House, Hawkins Road
Colchester, Essex CO2 8LA
United Kingdom
Phone: +44.0845.539.1200
Fax: +44.0845.539.1201
www.cyberneteurope.com
sales@cyberneteurope.com
support@cyberneteurope.com

Cybernet Taiwan Company, LTD.
4F., No.25, Lane 140, Xingai Rd
Neihu District, Taipei City 11494,
Taiwan (R.O.C.)
Phone: (02) 2790-4776
Fax: (02) 2793-3172
www.cybernet.com.tw
sales@cybernet.com.tw
support@cybernet.com.tw